## Lindy 3m Cat.6A U/UTP LSZH Cable, Grey 10pcs

## Brand : Lindy

Product code: 47623

Product name : 3m Cat.6A U/UTP LSZH Cable, Grey 10pcs

- Twisted Pair Patch Cable with RJ45 connectors
- Cat.6A U/UTP, LSZH
- Integrated snagless connector for latch protection
- Gold plated pins for better conductivity and elimination of signal loss
- 3m Cat.6A U/UTP LSZH Cable, Grey 10pcs

## Lindy 3m Cat.6A U/UTP LSZH Cable, Grey 10pcs:

Cat.6A U/UTP LSZH network cable with support for bandwidth up to 500MHz and features a snagless design with gold plated contacts for ethernet standards up to 1GBase-T.

Cat.6A cable for operating frequencies up to 500MHz. The unshielded version (U/UTP) can be used for Gigabit Ethernet thanks to the special design of the electrophysical parameters (NExT, FExT, etc.) Without the need for shielding. These cables are manufactured and tested according to the ISO/IEC 11801 specification.

The gold-plated contacts ensure reliable, corrosion-free connections over extensive periods of time. A robust snagless strain relief design prevents damage to the connector latch during installation and removal.





Features		Operational conditions	
Product colour * Cable length *	Grey 3 m	Operating temperature (T-T) Storage temperature (T-T)	-10 - 60 °C -20 - 75 °C
	Cat6a S/FTP (S-STP)	Sustainability	
Connector 1 *	S/FTP (S-STP) RJ-45	Doesn't contain	Halogen
Connector 2 *	RJ-45	Certificates	
Connector 1 gender *	Male	Compliance certificates	REACH, RoHS, UL
Connector 2 gender * Connector 1 form factor	Male Straight	Certification	RoHS, REACH, UL, California Proposition 65
Connector 2 form factor	Straight	Weight & dimensions	
Connector contacts plating	Nickel/Gold	Width	11.6 mm
Connector shielding	1	Depth	22.8 mm
Connector shield material	Aluminium	Height	8.3 mm
Jacket material	Low smoke zero halogen (LSZH)	Outer diameter	5.8 mm
Cable shape	Round Copper Polycarbonate (PC)	Packaging content	
Conductor material Connector housing material		Quantity per pack	1 pc(s)
Cabling technology	10GBase-T	Manual	✓
AWG wire size	26	Packaging data	
Frequency	500 MHz 6.9 cm	Package type	Box
Bend radius (min)		Logistics data	
		Warranty period	10 year(s)
		Technical details	

Sustainability compliance

1



## 4002888476232

**Catalog Object Cloud** 



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.